



MATERIALS
 1. TERMINAL: THERMAL PLASTIC (UL 94V-0)
 2. TERMINAL: COVER ALL OF GOLD PLATING
 3. ON CONTACT PIN PLATING ON DIAL
 4. CONTACT SHIELD: BRASS-TIN PLATING (0-0.001mm)
 5. BACK SHIELD: BRASS-NICKEL PLATING (0.001mm)
SPECIFICATION
 1. CURRENT RATING: 1.0 AMP. MAX.
 2. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC 2 RMS FOR ONE MINUTE
 3. INSULATION RESISTANCE: 100M OHMS MIN AT 100V DC
 4. CONTACT RESISTANCE: 50m OHMS MAX.
 5. OPERATING TEMPERATURE: -25°C TO 85°C
 6. DURABILITY: 1000 CYCLES
 7. TACTING FORCE: 30mN MAX.
 8. EXTRACTING FORCE: 60-80mN
 9. MAX PROCESSING TEMPERATURE: 210°C FOR 10-40 SECONDS (CU-TRAP PLASTIC)

REV	NOTES	DATE
A	MODIFIED	2005/09/22
B	MODIFY SCHEMATIC	2005/10/06
C	增加料號: APJ+2447-D01 APJ+2447-RS1	2005/11/02
D	增加料號: APJ+2447-BF5	2005/11/02
E	增加尺寸	2005/11/02
F	????	2006/07/15



PART NUMBER	A COLOR	B COLOR
APJ-2447-RJ8	AQUA(57C)	ORANGE(17C)
APJ-2447-C05	BLACK	White
APJ-2447-TA5	PINK(01C)	WHITE(08C)
APJ-2447-T5	PINK(01C)	Green(09C)
APJ-2447-D01	ORANGE	BLACK
APJ+2447-RS1	GREEN	Green
APJ+2447-H10	AQUA(57C)	PINK(01C)
APJ+2447-BF5	AQUA(57C)	PINK(01C)
APJ-2447-C05	BLACK	BLACK

單位(UNITS)	mm
數量(QTY)	N/A
材料(MTL)	SEE NOTE
處理(FINISH)	SEE NOTE
繪圖(DRAW)	

鏡榮企業有限公司

E GREEN ENTERPRISE CO., LTD.

圖名(NAME)

變壓 JACK 針孔 3.50mm 鏡榮的圖面 繪製者 吳志偉

頁數(PART NUMBER) APJ+2447-XXXX

圖號(DRAW NUMBER) RAJ-2447XXX

圖檔(FILE NAME.DWG) B.G.C.T/APP2

比例(SCALE) 1:1

圖號(SHEET) A4

頁次(PAGE) 1

圖號(DWG) 1

DIMENSIONS TOLERANCE

METRIC

0 ± 30

.00 ± 15

.000 ± .000

.0000 ± .000

ANG ± 2°

設計(DEN)

審核(CHEK)

核准(APP D)

繪圖(DRAW)

圖號(SHEET)

頁次(PAGE)

圖號(DWG)