





REV.	NOTES	DATE
A	RELEASED	2005/09/13



P.C.B. LAYOUT



NOTES:

1.MATERIAL

- 1.1 Insulator:PBT+30%Glass Fiber (UL94V-0)
- 1.2 Contact: Brass
- 1.3 Contact Plated: Gold / Tin Plated
- 1.4 Shell: Steel, Nickel Plated
- 1.5 Screw: Brass, Nickel Plated

2.SPECIFICATION

- 2.1 Current Rate: 5 Amps
- 2.2 Insulator Resistance: 5000MΩ Min. at 500V DC
- 2.3 Dielectric Strength: 1000V Per minute
- 2.4 Operation Temperature: -55°C to +105°C

PART NO.	PLATING	COLOR
A02+0914-2050	GOLD/TIN PLATED	BLACK
A02+0914-2550	GOLD/TIN PLATED	GREEN

單位(UNITS)	mm
數量(QTY)	N/A
材料(MTL)	SEE NOTE
處理(FINISH)	SEE NOTE

E-GREEN ENTERPRISE CO., LTD.

圖名(NAME)

DR9公辦附手金黑 5.08 無毒

料號(PART NUMBER)	A02+0914-2550
圖號(DRAW NUMBER)	RA0209142550
圖檔(FILE NAME .DWG)	E:GCT/A/02/091/5
比例(SCALE)	1/1
圖紙(SHEET)	A4
頁次(PAGE)	1
原次(ORIG.)	A

DIMENSIONS TOLERANCE

METRIC

.05 = ±.30
.00 = ±.20
.000 = ±.000
ANG. = ±2°