




REV.	NOTES	DATE
A	RELEASED	0303/06/26
B	????	14/12/2003
C	???? ①	0303/06/26
D	????	2303/06/26
E	????	0304/1/26




RECOMMEND P.C.B. LAYOUT
BOTTOM VIEW

MATERIALS

1. HOUSING : THERMOPLASTIC (UL 94V-0).
2. TERMINAL : COPPER ALLOY.
3. SHELL : STEEL.
4. SHELL BRACKET:SPCC DR BRASS
SPECIFICATION
1.CURRENT RATING : 5 AMP. MAX.
2.DIELECTRIC WITHSTANDING VOLTAGE :
1000V AC R.M.S. FOR ONE MINUTE.
3.INSULATION RESISTANCE : 1000M OHMS MIN. AT 500V DC.
4.CONTACT RESISTANCE : 30m OHMS MAX.
5.OPERATING TEMPERATURE : -55°C TO+105°C.
6.DURABILITY : 500 CYCLES.

Plat No.	PLATING
A02-09152-051	COLD/TIN PLATED
A20+9160-2255L	COLD/TIN PLATED??



??(UNITS)	mm	E-GREEN ENTERPRISE CO., LTD.
??(QT'Y)	N/A	
??(MT'L)	SEE NOTE	
??(FINISH)	SEE NOTE	
??(DRAW)	???	??(NAME)
??(CODE 'N)		9P公+15P 5.08母叉鎖鎖半金(L單形)
??(CHK'K)		??(PART NUMBER) A02-09152-051
??(APP 'D)		??(DRAW NUMBER) RA0209152051
		??(FILE NAME) .DWG\GCCBCVPT
		??(SCALE) 1/1
		??(SHEET) 1
		??(REV.) E