



MATERIALS:

INSULATOR:P.B.T.30%GLASS FIBER,UL94V-0

COLOR: BLACK,RED,BLUE,GREEN,

GREY,WHITE,ORANGE

PURPLE#242C YELLOW#108C

CONTACTS:BRASS OR PHOSPHOR BRONZE,

GOLD FLASH OVER NICKEL OR SELECTIVE GOLD

ELECTRICAL:

CURRENT RATING:1AMP.

CONTACT RESISTANCE:15M Ω MAX.

INSULATION RESISTANCE:1000M Ω MIN.

DIELECTRIC WITHSTANDING:500VAC

OPERATING TEMPERATURE:-55°C~+105°C

MAX PROCESSING TEMP:190D FOR 10 SEC.

DIMENSIONS

CONTACTS	A	B	C	D
BH-06	15.06	5.08	3.0	2.5
BH-08	17.90	7.62	3.0	
BH-10	20.14	10.16	3.0	
BH-12	22.67	12.70	3.0	
BH-14	25.22	15.24	3.0	
BH-16	27.60	17.78	3.0	
BH-20	32.68	22.86	3.0	
BH-24	38.32	27.94	3.0	4.5
BH-26	40.50	30.48	3.0	
BH-30	46.00	35.56	3.0	
BH-34	50.70	40.64	3.0	
BH-40	58.30	48.26	3.0	
BH-44	63.78	53.34	3.0	
BH-50	71.05	60.96	3.0	
BH-60	84.10	73.66	3.0	
BH-64	89.25	78.74	3.0	

BH-XXS-X-XX-N

PIN數

第PIN位置→20代表插第20PIN

顏色: 代表黑色R代表藍色W代表白色R代表紅色

UNSPECIFIED TOLERANCE	X ±0.2	.X ±0.2	.XX ±0.2	ITEM BH	MATERIAL PBT	Q'TY 0	TOOLING NO. 0	DRAWING CODE CTS-11	DRAWING NO. BH-00048
REVISION	DATE	DESCRIPTION	DRAWN BY	2003/04/16	BH-XXS-N	E-GREEN ENTERPRISE CO., LTD.		SCALE	EDITION
			DESIGNED BY					UNIT	A3
			APPROVAL BY						